



## Datasheet

### Matrix PAL+ Track spotlight

1002.9291

MATRIX PAL LED2500-965PAL 40 SR PRO ONF



<b>System power</b>	36 W
<b>Luminaire flux</b>	2500 lm
<b>Tunable White</b>	2500 -
<b>Colour temperature</b>	6500 K
<b>CRI</b>	CRI > 90
<b>UGR C0 4H/8H</b>	17
<b>UGR C90 4H/8H</b>	17
<b>Economic life-time</b>	L70 50'000 h
<b>Light control</b>	ON/OFF
<b>Ingress Protection</b>	IP20
<b>Finish</b>	silver

Track spotlight Matrix PAL+ with conductor track adaptor for three circuit track Global Trac Pro, with LED, system power: 36 W, luminous flux of luminaire 2500 lm, colour rendering index CRI > 90, colour temperature 2500 - 6500 K, colour tolerances SDCM 3, lifetime LED L70 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, 1 integral control gear, ON/OFF, control gear box in die-cast aluminium, reflector housing in die-cast aluminium, silver, (F), 40°,

protection class I, ingress protection IP20, glow wire test 650 °C, Ø = 127 mm, L = 175 mm, B = 92 mm, A = 210 mm, pivotable 360°, swivelling 45°