




## Datasheet

### Polar Universal Recessed directional spotlight

2003.1836

POLAR UNI DS CR176 LED4150-830 60 WH ONF



<b>System power</b>	35 W
<b>Luminaire flux</b>	4150 lm
<b>Colour temperature</b>	3000 K
<b>CRI</b>	CRI > 80
<b>UGR C0 4H/8H</b>	20
<b>UGR C90 4H/8H</b>	20
<b>Economic life-time</b>	L90 50'000 h
<b>Light control</b>	ON/OFF
<b>Ingress Protection</b>	IP20
<b>Finish</b>	white
<b>Weight</b>	1.2 kg

Recessed directional spotlight Polar Universal with LED, system power: 35 W, luminous flux of luminaire 4150 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 2, lifetime LED L90 50'000 h, 230 V, direct light emission, housing in die-cast aluminium, with ceiling trim, white, similar to RAL 9016, wide beam, (F), 60°, operating unit included in delivery, ON/OFF,

protection class II, ingress protection IP20, glow wire test 850 °C, this product contains a light source of energy efficiency class D and EPREL registration number: 864626  
 Ø = 192 mm, DAØ = 176 mm, ET = 140 mm, pivotable 360°, swivelling 90°